NOZZLE HEATERS

Nozzle heaters are used for blowers, injection moulding machines and extruders in the plastics industry, for example.

Nozzle heaters can be loaded up to 5 W/cm² and quickly bring the workpiece to a stable working temperature.

As standard, nozzle heaters are made of brass and have a 30° axial cable outlet with a 500 mm supply cable. The supply cable is protected by metal braid. The diameter can vary from Ø25 to Ø100 mm and the height from 20 to 90 mm. Max. temperature is 340°C. Power tolerance is +5% / -10%.

Custom built nozzle heaters can be manufactured in, for example, stainless steel, to other dimensions and with radial or tangential cable outlets.

STANDARD PROGRAMME

Item no.	Size	Voltage	Power
58802521	Ø25 x 25	230 V	85 W
58802547	Ø25 x 35	230 V	125 W
58803115	Ø30/31 x 20	230 V	85 W
58803123	Ø30/31 x 25	230 V	110 W
58803131	Ø30/31 x 30	230 V	135 W
58803149	Ø30/31 x 35	230 V	160 W
58803156	Ø30/31 x 38	230 V	185 W
58803172	Ø30/31 x 50	230 V	235 W
58803511	Ø34/35 x 20	230 V	95 W
58803958	Ø38/39 x 38	230 V	235 W
58804113	Ø40/41 x 20	230 V	125 W
58804121	Ø40/41 x 25	230 V	160 W
58804147	Ø40/41 x 35	230 V	235 W
58804154	Ø40/41 x 38	230 V	270 W
58804519	Ø44/45 x 20	230 V	125 W
58804535	Ø44/45 x 30	230 V	200 W
58804550	Ø44/45 x 38	230 V	270 W
58804568	Ø44/45 x 45	230 V	310 W
58804956	Ø48/49 x 38	230 V	300 W
58804915	Ø50/51 x 20	230 V	140 W
58805128	Ø50/51 x 25	230 V	185 W
58805136	Ø50/51 x 30	230 V	225 W
58805151	Ø50/51 x 38	230 V	310 W
58805524	Ø54/55 x 25	230 V	200 W
58805532	Ø54/55 x 30	230 V	245 W
58805557	Ø54/55 x 38	230 V	335 W
58806126	Ø60/61 x 20	230 V	170 W
58806134	Ø60/61 x 30	230 V	275 W
58806159	Ø60/61 x 38	230 V	375 W
58807132	Ø70/71 x 30	230 V	320 W
58807173	Ø70/71 x 50	230 V	560 W
58808189	Ø80/81 x 50	230 V	630 W
58808577	Ø84/85 x 50	230 V	670 W
58809591	Ø94/95 x 60	230 V	910 W
58802596	Ø100 x 60	230 V	970 W

05-2026 EN